



MATERIALS

Pump body	Technopolymer
Motor shaft	AISI 416
Impellers	Technopolymer
Suction base	Technopolymer

TECHNICAL FEATURES

Max. Head	9,8m
Max. Flow	13,5m ³ /h
Max. Liquid temperature	35°C
Insulation class	F
Poles	2
Protection degree	IP68
Voltage	230V (1ph)



Series: **DB NOVA UP**



Series: **DB NOVA UP ... MAE**
with **electronic float switch**

CODE	MOTOR POWER - AMPERE				Cable	Ø	Type	Free pass.	Q														
	kW	HP	1x230V 50Hz	µF	m	Inch			m³/h0	1	2	3	4,5	5	6	7	7,5	9	10	12	13,5		
									mm	l/min 0	16,6	33,6	50	75	83,3	100	116,6	125	150	166,6	200	225	
DB NOVA UP 300M A	0,21	0,28	1,5	8	10	1"1/4	AUT	10	76	69	63	56	47	44	36	28	23	1					
DB NOVA UP 300M	0,21	0,28	1,5	8	10	1"1/4	MAN	10	76	69	63	56	47	44	36	28	23	1					
DB NOVA UP 600M A	0,52	0,69	3,5	10	10	1"1/4	AUT	10	98	94	9	85	77	74	68	62	59	47	39	2	0,3		
DB NOVA UP 600M	0,52	0,69	3,5	10	10	1"1/4	MAN	10	98	94	9	85	77	74	68	62	59	47	39	2	0,3		
MAE models - WITH ELECTRONIC FLOAT SWITCH																							
DB NOVA UP 300MAE	0,21	0,28	1,5	8	10	1"1/4	AUT	10	76	69	63	56	47	44	36	28	23	1					
DB NOVA UP 600MAE	0,52	0,69	3,5	10	10	1"1/4	AUT	10	98	94	9	85	77	74	68	62	59	47	39	2	0,3		