PRESSURE BOOSTERS

Subgroup 260

Self priming pumps equipped with control device

APPLICATIONS

The pump is equipped with a control device, which ensures automatic operation of the pump. When a tap is opened, the pump starts running and automatically switches off as soon as the tap is closed. If the source (the place from which water is drawn) is empty, the control unit ensures that the pump automatically switches off. This is to prevent damage due to 'dry running'. Thanks to the already connected wiring between the pump and the pressure flow switches, you can start immediately! It can be used in several situations (Watering, spraying, watering the garden or lawn, cleaning of terraces, outdoor paving or garden furniture, emptying rooms or wells, feeding (rain) water to washing machines, toilets, sinks or showers from a separate water circuit)



Code: **P C JM 100 PRESSCWT**

available with inox pump (P SP JX 100 PRESSCWT)



Code: **P C JM 100 MONDIALPR**

available with inox pump (P SP JX 100 MONDIALPR)



Code: **P C JM 100 H2Q PC**

available with inox pump (P SP JX 100 H2Q PC)



Code: **P C JM 100 TK**

available with inox pump (P SP JX 100 TK)



Code: **P C JM 100 FSCB15**

available with inox pump (P SP JX 100 FSCB15)

N.B.: for pumps characteristics see pag. 66 (P C JM ...) and pag. 69 (P SP JX 100)
for the control device characteristics see from pag. 143 to pag. 150